

STARTUP STATE

This pedal features a soft-switch true bypass system with a save state for setting the power on state between bypassed and active. To change the state:

- Disconnect the power connection from the power jack, if not already done.

- While holding down the bypass switch, re-insert the power connection to the power jack. The bypass LED will blink four times.

- Release the bypass switch. The LED now represents the the saved power on state (LED on for "active", off for "bypass"). The pedal is ready to be used as normal. This setting will be permanently stored until this procedure is done again.

SPECIFICATIONS

Input Impedance	1M Ω m
Output Impedance	25k Ω m
Power Supply	9V DC Centre-Negative Plug, 2.1mm barrel
Current Draw	~25mA
Enclosure	Diecast Aluminum, Powdercoat Finish
Dimensions	11.4×6.8×4.9 cm (LxWxH)
Weight	0.270kg

Uses standard 9V centre-negative plug power adaptors only. Improper supply may cause permanent damage your unit. No battery clip is provided. Best results for noise reduction require a good quality isolated power supply.

WARRANTY

All products are covered under warranty and are subject to Australian consumer laws. View our warranty information by visting <http://www.crowella.org/warranty>

All specifications listed, inclusive of both internal and external representations of products and specifications are subject to change at short notice. For further information and support, you can either visit <http://www.crowella.org> or contact support@crowella.org

The manufacturer claims that the product fulfils the following requirements set by RoHS and WEEE.

ANIMATED

OVERDRIVE

USER MANUAL



CROWELLA EFFECTS - AUSTRALIA

INTRODUCTION

Thank you very much for choosing the **ANIMATED** overdrive pedal to become a piece of your tonal landscape!

Loved by bassists around the world for it's signature gnarling attack and distinctive bite, this pedal provides incomprehensible levels of gain and drive while offering a blend of the original signal to keep yourself truly present within a mix. Cut above the rest and let all the energy flow out.

This manual will provide more information on getting started and understanding the features available to you. Enjoy your new pedal!

Adam Crowell
Founder of Crowella Effects

CONTROLS AND OVERVIEW

POWER
9V DC Centre-Negative Plug, 2.1mm jack.
Minimum current draw 25mA

TONE
Dials in your tone from removing treble to adding bite.

BLEND
Blends between a dry signal (unaffected signal at unity gain) and a wet signal (full effect). This interacts with the level control to mix the overall sound.

OUTPUT
Signal out. Plug into your amp or next pedal.

DIST
Control your input gain to go from subtle drive to distorted.

LEVEL
Sets the output level of the distorted signal.

INPUT
Your guitar or bass goes in here

BYPASS
Controls the active/bypass state. LED lights up for active effect. When LED is off, the effect is bypassed

9V DC

TONES

DIST

BLEND

LEVEL

ANIMATED OVERDRIVE

OUTPUT

INPUT

CROWELLA EFFECTS - AUSTRALIA